

www.check-flex.eu www.check-flex.co.uk





SECTION A-A

Bill of Materials		
Item No.	Description	Material
1	Check-Flex G5M-S0100	NN
2	Internal Expandable Clamp	316 SS

Notes:

1. Dimensions are approximate and may change due to pipe dimension, inlet pressure, back pressure and flow rates.
2. Minimum valve overall length 191mm
3. Installation, Operation & Maintenance Manuals contact Check-Flex®: info@check-flex.eu
4. Elastomer: Neoprene to ASTM D2000: 5BC520 A14 C12 Eo34 G21 Z1 Z1= flame resistance per ASTM C1166

Meets and exceeds: D412 modulus (300%) D573 heat age test D1171 ozone resistance

Nominal Diameter	Qty.	Pipe I.D.	Clamp Installation Position	Standard Valve Dimensions		Flow Data					Approx. Weight
				Cuff Width	Length	Flow Media	Max. Flow Rate	Max. Flow Velocity	Line Pessure	Back Pessure	
mm				mm	mm						kgs
51.9			DISCHARGE END	30	180						0.55



Check-Flex® G5M-S0050 Inline Check Valve

Check-Flex®

Check-Flex G5M-S0050

PROJECT NOTES:

PROJECT NAME:

CUSTOMER:

SIZE	SCALE	DRAWING No.	SHEET
A	NTS		1 OF 1